

5 iOLM Pack and Features table



PACK/OPTIONS	FEATURES	MAXTESTER					FTB-1		FTB-1v2/PRO					FTB-2/PRO FTB-4-PRO					FTB-500			
		MAX-715B	MAX-720B	MAX-730B	MAX-720C	MAX-730C	FTB-720/G	FTB-730/G	FTB-720C/Gv2	FTB-730C/Gv2	FTB-740C/Gv2	FTB-735C	FTB-750C	FTBx-720C	FTBx-730C	FTBx-735C	FTBx-740C	FTBx-750C	FTB-7300E	FTB-7400E	FTB-7300E	FTB-7400E
iOLM Standard	Dynamic multipulse acquisition	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Intelligent trace analysis	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Link view	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Intelligent Diagnosis	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	SOR OTDR trace generation	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Single iOLM file per link for easy reporting	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Optimode : Fast Short link	✓	✓	✓	✓	✓	✗	✗	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗
	Optimode : Short-link close events	✗	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓
iOLM Advanced (iADV) ¹	Real-time acquisition	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Custom elements	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Advanced link edition and re-analysis	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	2:N splitter characterization	✗	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓
	Optimode : PON last-mile certification	✓	✗	✓	✗	✓	✗	✓	✗	✓	✗	✓	✗	✗	✗	✓	✗	✗	✓	✗	✓	✗
iOLM PRO ¹ (iPRO - includes iADV and iLOOP)	Automated MPO cable characterization and troubleshooting (with EXFO switch) (iMF)	✗	✗	✗	✗	✗	✓	✓	✓	✓	✗	✓	✓	✓	✓	✗	✓	✗	✗	✗	✗	
iLOOP ¹	iOLM Loopback (iLOOP)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
iCERT ¹	Cabling Certification option	✗	✗	✗	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓

(1) = Require enabling iOLM standard